

# P-9911(F) Fixed Fire Telephone Handset



## Description

The fixed handset is wall mounted, available for surface mount. The unit should be mounted in a suitable and dry location at about 1.5m from finished floor level. Common installation positioning is in the landing levels of all core stairwells and escape routes, although the exact positioning is the responsibility of the project designer.

## Technical Specification

- Frequency Range: 300Hz to 3400Hz
- Ring Sound: >70dB(A)
- Dimension: 234mm X 146mm X 60mm
- Operating Temperature: 0°C to 40°C
- Relative Humidity: 45% - 95%, non-condensing

## Order Information

Part No.	P-9911(F)
Device Name	Fixed Fire Telephone Handset
Product No.	30500144
Compatible Products	GST-FT8WN Fire telephone panel GST-FT24N Fire telephone panel P-9911(H) Hands-free fire telephone

IMPORTANT: This publication is a generic version in which product information is shown for informational purposes only and does not constitute a specific commitment or guarantee. We are constantly pursuing the improvement of product technology to improve product performance, for which we reserve the right to adjust the configuration and technical information of the related products without notice. In addition, the description of system performance in this publication applies only to the usual situation. As a result, there may be a variety of unpredictable special circumstances in the real world, so the realization of the relevant product performance will depend on the professional investigation and analysis and the design plan. Please contact us and we will be happy to provide you with professional advice.