

# P-9911(H) Hands-free Speaker Fire Telephone



## Description

The P-9911(H) hands-free speaker fire telephone communication point is compatible with the GST- FT series of fire telephone panels, for emergency communication over a dedicated hard wired system normally located with the fire command centre.

## Order Information

Part No.	P-9911(H)
Device Name	Hands-free Speaker Fire Telephone
Product No.	30500288
Compatible Products	GST-FT8WN Fire telephone panel GST-FT24N Fire telephone panel P-9911(F) Fixed fire telephone handset P-9911(J) Fire telephone Jack

## Technical Specification

- Standby Current: 0.4mA
- Operating Current: <30mA
- Frequency Range: 300Hz to 3400Hz
- Ring Sound: ≥70dB(A)
- Dimension: 160mm X 80mm X 34mm
- Environment Temperature: -10°C to 55°C
- Relative Humidity: ≤95%, non condensing

IMPORTANT: This publication is a generic version in which product information is shown for informational purposes only and does not constitute a specific commitment or guarantee. We are constantly pursuing the improvement of product technology to improve product performance, for which we reserve the right to adjust the configuration and technical information of the related products without notice. In addition, the description of system performance in this publication applies only to the usual situation. As a result, there may be a variety of unpredictable special circumstances in the real world, so the realization of the relevant product performance will depend on the professional investigation and analysis and the design plan. Please contact us and we will be happy to provide you with professional advice.